

## Pipe Inspection Camera System P10000DK

Application: Pipe/Sewer/Drain/Borehole



### Feature:

1.  $\varnothing$  23mm pipe ,suit for  $\varnothing$  25mm- $\varnothing$  200mm pipe. Waterproof IP68
2. 600TVL, 1/4" CMOS sensor
3. Resolution: PAL 720\*576; NTSC:720\*480
4. Video/audio/Text recording
5.  $\varnothing$  5.2mm fiberglass rod, 20M-50M available
6. 8inch TFT-LCD Monitor
7. 6600MA built-in Li-ion battery and AC110V-240V 1.5A Adaptor
8. Engineer Plastic ABS carry case

\*Patent Pending Design \*

## Detail Parts Spec:

|   |  |
|---|--|
|     | <ul style="list-style-type: none"><li>* Camera head size <math>\Phi 23 \times 53\text{mm}</math> for pipe <math>\Phi 25</math> to <math>200\text{mm}</math></li><li>* 600TVL 1/4" CMOS camera</li><li>* Camera head casing material stainless steel</li><li>* Total Pixels PAL 720X576 NTSC 720X 480</li><li>* Field of view <math>120^\circ</math>, IP68 waterproof</li><li>* 12 pcs high intensity white LED</li></ul> |
|    | <ul style="list-style-type: none"><li>* 8 inch TFT LCD monitor</li><li>* 800x600 pixels</li><li>* 4:3 display model</li><li>* Brightness: 400cd/m<sup>2</sup></li><li>* Sun shield and remote control included</li></ul>   |
|   | <ul style="list-style-type: none"><li>* DVR control buttons</li><li>* SD card (max 64G) jack, keyboard jack</li><li>* LED brightness adjusting knob</li><li>* A / V &amp; photo selection available</li><li>* On/off microphone control button</li><li>* Battery level indicator lights</li><li>* Video / audio output to another screen</li></ul>   |
|  | <ul style="list-style-type: none"><li>* Fibreglass push rod cable</li><li>* Cable diameter <math>\Phi 5.2\text{mm}</math></li><li>* Cable length from 20m to 50 optional</li><li>* Reel size <math>\Phi 320 \times 110\text{mm}</math></li></ul>   |
|  | <ul style="list-style-type: none"><li>* 6600mAh li-ion battery</li><li>* AC 110V-240V 1.5A power charger</li><li>* Charging time 5 hours, working time 6 hours</li></ul>   |
|  | <ul style="list-style-type: none"><li>* Case size: 520 x 435 x 200mm</li><li>* Unit operating temperature: -10 to 50 degrees Celsius, RH 95% maximum</li><li>* Storage temperature: - 20 to 70 degrees Celsius, RH 95% maximum</li></ul>   |

Total weight 26KG(2units)

Packing carton size: 53.8CM\*43.8CM\*48CM.(2units)

\*Patent Pending Design \*

**ROYAL TOOL(HONGKONG)LIMITED**  
No. 38, Mingquan Road, Zhongshan city,  
Guangdong Province, China 528400.  
E-mail: info@royaltoolpro.com  
Tel: 086 0760 8880 1865  
www.royaltoolpro.com