

# Compact 1.3MP AHD Pan and Tilt Pipe Inspection Camera System P10002PTCM-1

Application: Pipe/Sewer/Drain/Borehole



### Feature:

- 1.360 degree rotation camera head,pan 360°,tilt180°.
- 2.1/3 CMOS,1.3MP.AHD camera head, waterproof up to 10bars.
- 3. Compact and integrated DVR control unit, easy operation.
- 4. Waterproof 8Inch display, anti-shake and work for rugged environment
- 5.video/audio/text recording.
- 6.60m/120m cable length, Ø9mm fiberglass.
- 7.USB bluetooth, keyboard to typewrite the words.
- 8. Camera video resolution: 720 P.
- 9.Built-in 8800mA Li-ion battery, support unit working more than 6 hours.
- 10. Digital meter-counter function, error is less than 1%

\*Patent Pending Design \*

ROYAL TOOL(HONGKONG)LIMITED

No. 38, Mingquan Road, Zhongshan city, Guangdong Province, China 528400. E-mail:info@royaltoolpro.com
Tel:086 0735 7640 815/086 0760 8880 1865 www.royaltoolpro.com

# Detail Parts Spec:

# \* Camera size Ø50mm x 154mm, sensor 1/3" CMOS ,1.3MP pixel \* Waterproof IP68 up to 10 bar \* View range 120° \* Rotation: Pan 360°, Tilt 180° \* lens position automatic reset \* Slip coupling for rotation axle

\* 6pcs high light LED lighting adjustable\* Detachable with pins type connection to Cable Reel

Detachable with pins type connection to Cable Re-

\* Lens window sapphire glass

### Multiple DVR &Control Panel

\*8"HD IPS LCD Screen, 1280X720 resolution, 16:9 display model

\*HD DVR SYSTEM with recording 720P video

\*DVR recording system with AVI video format

\*Waterproof LCD panel

\*USB wireless Keyboard real time typewriting

\* USB port to connect storage device (16G USB flash disk)

\* Built-in 7000mA rechargeable Li-ion Battery Pack

\*Battery level indicator

\* Sunshade is included


\* Box size 23x20x5cm

\*AC 110V-240V 1.5A power charger


\*Charging time 7 hours, working time about 4 hours

\*Can fix on the cable reel, can be handhold, can hang on the neck(optional)

Multiple DVR Functions Instruction



- 1. POWER Press the button for 3 seconds to turn on /off the control box
- 2. Keboard Insert 2.4G wireless keyboard adaptor
- 3.USB Insert external USB disk to record and save the video& picture files. Please don't remove the USB flash disk when it is recording
- 4.Audio Insert the 3.5mm earphone
- 5. Counter Use 8pin link cable, one port to "COUNTER" port, the other to cable reel "Meter counter port".
- 6.Camera Connect 6pin link cable to cable reel
- 7. Control Panel Details reference picture(1-1)
- 8.Monitor 8inch HD screen ,1280x720 resolution
- 9.Led Dimmer Adjust 18mm,23mm,29mm,40mm and 55mm camera LED brightness
- 10.DC IN Connecting extra charge adaptor
- 11.RESET When the system is halted



## Digital Meter-counter Cable

- \* Fiberglass push rod cable
- \* Cable diameter ø9mm
- \* Cable length from 60m to 150m optional
- $^{\star}$  Wheel with a tray for lay the keyboard, screen and keyboard can 360  $^{\circ}$  rotate
- \* Reel size 70 x 28 x 84cm
- \*Reel brake available
- \* Updated digital meter counter, error rate less than 1%

### Carry Bag





\*Size: 32x22x25cm

\*Easy to carry

\*Include: Camera head/Control unit/Wireless keyboard/Test cable/Link cable/User mannual

•	* 8800mA li-ion battery
	* AC110V-240V 1.5A power charger
	* Charging time 5 hours, working time 6 hours
Skid(Standard configuration)	* Big skids: Φ146mm
,	* Small skids: Ф85mm
	Cinali diago. 4 commi
Skid1 (Extra Option)	* Material: Stainless steel
Po	* Six wheels on this skids
V	* Min Diameter is 200mm
	* Max Diameter is 500mm
Skid2(Extra Option)	*Stainless steel & nylon
- 4	* size adjustable
	* Min Dia.155mm Max Dia.370mm (optional)
	* Min Dia 200mm Max Dia.500mm (optional)
(3)	
Skid3 (Extra Option)	*Stainless steel & nylon
	* size adjustable
	* Min Dia 200mm Max Dia.450mm (optional)

Gross weight:60M 30KG 120M 36KG

Packing cartons size: 84.5x43.5x93cm 40X30X30cm

\*Patent Pending Design \*