# ROYALTOOL

# Built-in DT Senspr Marine Network Camera Video System with Window System and GPS D10000(upgrade option)

Application: widely used in aquaculture (fish, sea cucumber, etc.).underwater wedding photography, submarine marine life research, water pipe pile hole imaging, downhole TV, underwater investigation, underwater operations (such as checking the cage hole), diving adventure, underwater engineering acceptance, downhole observation (such as drilling wells), leisure, fishing, etc.;











#### **Performance**

- Ø70MM,4K full HD Camera Head.Can be permanently fixed sea water
- Built-in led lights and infrared lights.
- 1/2.8 sensor,5.5MM Lens
- Water depth: 100M
- Subcon end connector
- Deep sensor
- Temperature sensor
- Suitcase with GPS function
- 10 inch HD display, Split screen is available.
- Windows system
- 500G Hard Driver
- External 2USB jackets and support mouse operation
- External 2 RJ45 jackets and support LAN/WAN
- H.264 and AVI video format
- \* Patent Pending Design \*

### ROYAL TOOL(HONGKONG)LIMITED

No. 38, Mingquan Road, Zhongshan city, Guangdong Province, China 528400. E-mail:info@royaltoolpro.com
Tel:086 07357640815/086 0760 8880 1865
www.royaltoolpro.com
www.vanhonindustry.com

Spec Detail:	
Dispaly	
Screen	10 inch SPI HD display,170° wide view angle.
Split Screen	Available
Waterproof	IP65 waterproof rating, to prevent jet water immersion
OSD language	English
Suitacase	
DVR	support for video, playback, query, copy and so on; controlling the display function
Audio	audio input, you can record the sound through the microphone, stored to the hard disk
GPS	Built-in GPS function, accuracy:5M
External Jacket1	2pcs external RJ45 jacket, support WAN/LAN
External Jacket2	2pcs external USB jackets
Video input	4K/5MP/4MP/3MP/2MP 60fps
Storage	built-in 500GB hard drive, long time storage 1080P HD video
Special	anti-knock, effectively ensure that the internal components of normal work
Software	Built-in Widows system
Waterproof	IP65 waterproof rating, to prevent the jet of water immersion
Mouse	support the mouse for quick operation
Video format	H.264 and AVI
Built-in Battery	Buit-in 6000mAh rechargeable battery, support 6 continuous work time.
Power Supply	DC24V
• • •	25.2V
Adaptor	
Demension	36.7cm*29.6cm*15.3cm
Gross/Net Weight	4.5KG/4KG
Camera Head	
Demension	Ø70*140mm
Lens	5.5mm (H.FOV:90°)
Sensor	1/2.8" SONY CMOS sensor ,color 0.001Lux F1.2,black/white 0.0001Lux F1.2
Resolution	4K 30FPS
Temperature sensor	Built-in
Deep sensor	Built-in
Illumination	Light sensor contorlled 3 white light , 4 infrared light, 10 level brightness settings
Material	316L stainless steel, anti-corrosion
Waterproof	IP68
Water Depth	Maximum 1000Kpa (Waterpressure resisitance 100M)
Cable	The default length is 10 meters (the longest is no more than 80 meters),PU material,diameter 6.7MM.Resistance to 60KG pull,Anti-aging,Anti-friction,Resistance to
Cable length	seawater corrosion, Special underwater wire.  Standard 20M-80M; If 80M-120M, 120M-300M it will be an customized option.
Cable end	Subcon cable end connector. Cable detachable from the camera head
supporting device	Support iOS, Android, computer, NVR.Compatible with hikvision, dahua, proprietary protocol.(Only support windows-IE browser for camera internal parameter setting)
supporting agreement	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF;SDK Secondary development
Use environment	Sea water / fresh water /Underwater,land,Car,Shipborne.
Working humidity	0%-100%
working temperature	-20°~55°
Telescopic Pole(Option)	
Packing List	

<sup>\*</sup> Patent Pending Design \*

1\*100M cable

1\*Charger

1\*suitcase 1\*Mouse

### ROYAL TOOL(HONGKONG)LIMITED

No. 38, Mingquan Road, Zhongshan city, Guangdong Province, China 528400. E-mail:info@royaltoolpro.com
Tel:086 07357640815/086 0760 8880 1865

Phone: 086 18565801348 www.royaltoolpro.com www.vanhonindustry.com